

- When you are finished using the device, set all switches to **Off/0** and unplug the power cable from the mains.
- Only use extension cables if you have first ensured that they are in good condition.
- If the device's power cable has been damaged, it must only be replaced by an authorized service centre.
- Never allow children to play with the packaging. This poses a suffocation risk.

Disposal

Electrical tools, accessories and packaging must be recycled in an environmentally friendly manner.

For EU countries only



Never dispose of electrical tools as household waste! In accordance with the European Directive 2002/96/EC on Waste Electrical and Electronic Equipment and its implementation into national law, electrical tools that are no longer suitable for use must be sorted separately and recycled in an environmentally friendly manner.

Within the EU, this symbol indicates that this product must not be disposed of as household waste. Waste equipment contains valuable recyclable materials that should be supplied for recycling; this also avoids causing damage to the environment or human health through uncontrolled waste disposal. Please therefore dispose of waste equipment via suitable collection systems or return the device to the place where you bought it for disposal. They will then submit the device for recycling.

Accumulators and batteries

Never put accumulators/batteries into household waste, water or fire. Accumulators/batteries should be collected, recycled or disposed of in an environmentally friendly manner.

For EU countries only

In accordance with Directive 91/157/EEC, defective or used accumulators/batteries can be submitted directly to Canbolat Vertriebsgesellschaft mbH, Rotkreuzstr. 10, D-97080 Würzburg, Germany

Specification of replacement parts to be used

The device is supplied without replacement parts. If replacement parts are required, please contact our service department on 0931/47 08 8387.

Technical details

Type of device	Personal-care device for manicure and pedicure
Speed	20,000 revolutions per minute
Power supply	220-240 V / 50 Hz
Rated output voltage	DC 0-17 V
Rated power	0,8A
Output current	ca. 39 dB
Loudness	1,40 kg
Weight	0,8A

Transport/storage/operating conditions

Transport	Only transport in original packaging.
Transport and storage temperature:	+5° C to +50° C
Operating temperature	+10° C to +40° C
Atmospheric pressure	700-1060 hPa

Abrupt temperature changes should be avoided because of the risk of condensation forming in the device; do not use the device until the temperature has equalized.